

Safety Data Sheet


according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: January 02, 2020

1 Identification

- **Product identifier**
- **Trade name:** **CCASA-WFTC**
CARB COMPLIANT ADHESIVE WEB FAST TACK
- **Product code:** 5164
- **Recommended use and restriction on use**
- **Recommended use:** Industrial uses.
- **Restrictions on use:** No relevant information available.
- **Details of the supplier of the Safety Data Sheet**
- **Manufacturer/Supplier:**
DURO DYNE CORPORATION
81 Spence Street
Bay Shore, NY 11706
800-899-3876
- **Emergency telephone number:**
ChemTel Inc.
(800)255-3924 (North America)
+1 (813)248-0585 (International)

2 Hazard(s) identification

- **Classification of the substance or mixture**
Flam. Aerosol 1 H222 Extremely flammable aerosol.
Press. Gas H280 Contains gas under pressure; may explode if heated.
Eye Irrit. 2A H319 Causes serious eye irritation.
Skin Sens. 1 H317 May cause an allergic skin reaction.
STOT SE 3 H336 May cause drowsiness or dizziness.
Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.
- **Label elements**
- **GHS label elements**
The product is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms:**

GHS02 GHS04 GHS07 GHS08
- **Signal word:** Danger
- **Hazard statements:**
H222 Extremely flammable aerosol.
H280 Contains gas under pressure; may explode if heated.
H319 Causes serious eye irritation.
H317 May cause an allergic skin reaction.
H336 May cause drowsiness or dizziness.
H304 May be fatal if swallowed and enters airways.
- **Precautionary statements:**
P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
P211 Do not spray on an open flame or other ignition source.

(Cont'd. on page 2)

Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: January 02, 2020

Trade name: CCASA-WFTC
CARB COMPLIANT ADHESIVE WEB FAST TACK

(Cont'd. of page 1)

P251	Pressurized container: Do not pierce or burn, even after use.
P261	Avoid breathing mist, vapors, or spray.
P264	Wash thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.
P272	Contaminated work clothing must not be allowed out of the workplace.
P280	Wear protective gloves and eye protection.
P301+P310	If swallowed: Immediately call a poison center/doctor.
P331	Do NOT induce vomiting.
P302+P352	If on skin: Wash with plenty of soap and water.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P312	Call a poison center/doctor if you feel unwell.
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P337+P313	If eye irritation persists: Get medical advice/attention.
P363	Wash contaminated clothing before reuse.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P405	Store locked up.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Other hazards** There are no other hazards not otherwise classified that have been identified.

3 Composition/information on ingredients

· **Chemical characterization: Mixtures**

· **Components:**

Component ID	Component Name	Concentration
67-64-1	Acetone ⚠ Flam. Liq. 2, H225 ⚠ Eye Irrit. 2A, H319; STOT SE 3, H336	20-<50%
79-20-9	Methyl acetate ⚠ Flam. Liq. 2, H225 ⚠ Eye Irrit. 2A, H319; STOT SE 3, H336	10-<20%
74-98-6	Propane ⚠ Flam. Gas 1, H220 ⚠ Press. Gas, H280 Simple Asphyxiant	10-<20%
106-97-8	butane ⚠ Flam. Gas 1, H220 ⚠ Press. Gas, H280 Simple Asphyxiant	10-<20%
64742-49-0	Naphtha (petroleum), hydrotreated light (Nota P, <0.1% benzene) ⚠ Flam. Liq. 2, H225 ⚠ Asp. Tox. 1, H304	5-<10%
98-56-6	4-chloro- α,α,α -trifluorotoluene ⚠ Flam. Liq. 3, H226 ⚠ Skin Sens. 1B, H317	1-<5%

(Cont'd. on page 3)

Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: January 02, 2020

**Trade name: CCASA-WFTC
CARB COMPLIANT ADHESIVE WEB FAST TACK**

(Cont'd. of page 2)

	Eye Irrit. 2B, H320	
142-82-5	Heptane ----- ⚠ Flam. Liq. 2, H225 ⚠ Asp. Tox. 1, H304 ⚠ Skin Irrit. 2, H315; STOT SE 3, H336 Eye Irrit. 2B, H320	1-<5%
841251-34-1	Maleic acid anhydride - modified polyisoprene, liquid ----- ⚠ Skin Sens. 1, H317	1-<5%
108-87-2	methylcyclohexane ----- ⚠ Flam. Liq. 2, H225 ⚠ Asp. Tox. 1, H304 ⚠ Skin Irrit. 2, H315; STOT SE 3, H336	0.1-<1%

· **Additional information:**

For the listed ingredient(s), the identity and/or exact percentage(s) are being withheld as a trade secret.
For the wording of the listed Hazard Statements, refer to section 16.

4 First-aid measures

· **Description of first aid measures**

· **After inhalation:**

Supply fresh air.

Provide oxygen treatment if affected person has difficulty breathing.

If experiencing respiratory symptoms: Call a poison center/doctor.

In case of unconsciousness place patient stably in side position for transportation.

· **After skin contact:**

Immediately remove any clothing soiled by the product.

Immediately wash with water and soap and rinse thoroughly.

If skin irritation or rash occurs: Get medical advice/attention.

· **After eye contact:**

Remove contact lenses if worn.

Rinse opened eye for several minutes under running water. Then consult a doctor.

· **After swallowing:**

Unlikely route of exposure.

Rinse out mouth and then drink plenty of water.

Do not induce vomiting; immediately call for medical help.

A person vomiting while lying on their back should be turned onto their side.

· **Most important symptoms and effects, both acute and delayed:**

Breathing difficulty

Dizziness

Coughing

Allergic reactions

Gastric or intestinal disorders when ingested.

Causes eye irritation.

Headache

Disorientation

· **Danger:**

May be fatal if swallowed and enters airways.

Danger of impaired breathing.

(Cont'd. on page 4)

Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: January 02, 2020

**Trade name: CCASA-WFTC
CARB COMPLIANT ADHESIVE WEB FAST TACK**

(Cont'd. of page 3)

May cause drowsiness or dizziness.

· **Indication of any immediate medical attention and special treatment needed:**

If swallowed or in case of vomiting, danger of entering the lungs.

Medical supervision for at least 48 hours.

If necessary oxygen respiration treatment.

Later observation for pneumonia and pulmonary edema.

Contains 4-chloro- α,α,α -trifluorotoluene, Maleic acid anhydride - modified polyisoprene, liquid. May produce an allergic reaction.

Treat skin and mucous membrane with antihistamine and corticoid preparations.

If medical advice is needed, have product container or label at hand.

5 Fire-fighting measures

· **Extinguishing media**

· **Suitable extinguishing agents:**

Water spray

Water fog / haze

Alcohol resistant foam

Carbon dioxide

Gaseous extinguishing agents

· **For safety reasons unsuitable extinguishing agents:** Water stream.

· **Special hazards arising from the substance or mixture**

Danger of receptacles bursting because of high vapor pressure if heated.

Extremely flammable aerosol.

During heating or in case of fire poisonous gases are produced.

· **Advice for firefighters**

· **Protective equipment:**

Wear self-contained respiratory protective device.

Wear fully protective suit.

· **Additional information:**

Eliminate all ignition sources if safe to do so.

Leaking gas fire: Do not extinguish, unless leak can be stopped safely.

Cool endangered receptacles with water in flooding quantities.

6 Accidental release measures

· **Personal precautions, protective equipment and emergency procedures**

Isolate area and prevent access.

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation.

Use respiratory protective device against the effects of fumes/dust/aerosol.

Protect from heat.

· **Environmental precautions**

Do not allow to enter sewers/ surface or ground water.

Inform respective authorities in case of seepage into water course or sewage system.

· **Methods and material for containment and cleaning up**

Allow to evaporate.

(Cont'd. on page 5)



Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: January 02, 2020

Trade name: CCASA-WFTC
CARB COMPLIANT ADHESIVE WEB FAST TACK

(Cont'd. of page 4)

In case of leaking material, use absorbent to contain leak. Rinse thoroughly with water.
 Send for recovery or disposal in suitable receptacles.

- **Reference to other sections**

- See Section 7 for information on safe handling.

- See Section 8 for information on personal protection equipment.

- See Section 13 for disposal information.

7 Handling and storage

- **Handling**

- **Precautions for safe handling:**

- Avoid splashes or spray in enclosed areas.

- Use only in well ventilated areas.

- Avoid contact with the eyes and skin.

- Handle with care.

- Avoid breathing mist, vapors, or spray.

- Keep out of reach of children.

- **Information about protection against explosions and fires:**

- Danger of receptacles bursting because of high vapor pressure if heated.

- Emergency cooling must be available in case of nearby fire.

- Flammable gas-air mixtures may be formed in empty containers/receptacles.

- **Conditions for safe storage, including any incompatibilities**

- **Requirements to be met by storerooms and receptacles:**

- Observe official regulations on storing packagings with pressurized containers.

- **Information about storage in one common storage facility:**

- Store away from foodstuffs.

- Do not store together with oxidizing and acidic materials.

- **Further information about storage conditions:**

- Store in a cool place. Heat will increase pressure and may lead to the container bursting.

- **Specific end use(s)** No relevant information available.

8 Exposure controls/personal protection

- **Control parameters**

- **Components with limit values that require monitoring at the workplace:**

- 67-64-1 Acetone**

PEL (USA)	Long-term value: 2400 mg/m ³ , 1000 ppm
REL (USA)	Long-term value: 590 mg/m ³ , 250 ppm
TLV (USA)	Short-term value: 1187 mg/m ³ , 500 ppm Long-term value: 594 mg/m ³ , 250 ppm BEI
EL (Canada)	Short-term value: 500 ppm Long-term value: 250 ppm
EV (Canada)	Short-term value: 750 ppm Long-term value: 500 ppm

(Cont'd. on page 6)



Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: January 02, 2020

Trade name: CCASA-WFTC
CARB COMPLIANT ADHESIVE WEB FAST TACK

(Cont'd. of page 5)

LMPE (Mexico)	Short-term value: 750 ppm Long-term value: 500 ppm A4, IBE
79-20-9 Methyl acetate	
PEL (USA)	Long-term value: 610 mg/m ³ , 200 ppm
REL (USA)	Short-term value: 760 mg/m ³ , 250 ppm Long-term value: 610 mg/m ³ , 200 ppm
TLV (USA)	Short-term value: 757 mg/m ³ , 250 ppm Long-term value: 606 mg/m ³ , 200 ppm
EL (Canada)	Short-term value: 250 ppm Long-term value: 200 ppm
EV (Canada)	Short-term value: 755 mg/m ³ , 250 ppm Long-term value: 605 mg/m ³ , 200 ppm
LMPE (Mexico)	Short-term value: 250 ppm Long-term value: 200 ppm
74-98-6 Propane	
PEL (USA)	Long-term value: 1800 mg/m ³ , 1000 ppm
REL (USA)	Long-term value: 1800 mg/m ³ , 1000 ppm
TLV (USA)	refer to Appendix F in TLVs&BEIs book; D, EX
EL (Canada)	Simple asphyxiant; EX
EV (Canada)	Long-term value: 1,000 ppm revoked as of 01/01/18
LMPE (Mexico)	Long-term value: 1000 ppm
106-97-8 butane	
REL (USA)	Long-term value: 1900 mg/m ³ , 800 ppm
TLV (USA)	Short-term value: 2370 mg/m ³ , 1000 ppm (EX)
EL (Canada)	Short-term value: 1000 ppm EX
EV (Canada)	Long-term value: 800 ppm revoked as of 01/01/18
LMPE (Mexico)	Long-term value: 1000 ppm
142-82-5 Heptane	
PEL (USA)	Long-term value: 2000 mg/m ³ , 500 ppm
REL (USA)	Long-term value: 350 mg/m ³ , 85 ppm Ceiling limit value: 1800* mg/m ³ , 440* ppm *15-min
TLV (USA)	Short-term value: 2050 mg/m ³ , 500 ppm Long-term value: 1640 mg/m ³ , 400 ppm
EL (Canada)	Short-term value: 500 ppm Long-term value: 400 ppm
EV (Canada)	Short-term value: 2045 mg/m ³ , 500 ppm Long-term value: 1635 mg/m ³ , 400 ppm

(Cont'd. on page 7)

Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: January 02, 2020

**Trade name: CCASA-WFTC
CARB COMPLIANT ADHESIVE WEB FAST TACK**

(Cont'd. of page 6)

LMPE (Mexico)	Short-term value: 500 ppm Long-term value: 400 ppm
---------------	---

108-87-2 methylcyclohexane

PEL (USA)	Long-term value: 2000 mg/m ³ , 500 ppm
REL (USA)	Long-term value: 1600 mg/m ³ , 400 ppm
TLV (USA)	Long-term value: 1610 mg/m ³ , 400 ppm
EL (Canada)	Long-term value: 400 ppm
EV (Canada)	Long-term value: 1,600 mg/m ³ , 400 ppm
LMPE (Mexico)	Long-term value: 400 ppm

· Ingredients with biological limit values:

67-64-1 Acetone

BEI (USA)	50 mg/L Medium: urine Time: end of shift Parameter: Acetone (nonspecific)
-----------	--

· Exposure controls

· General protective and hygienic measures:

The usual precautionary measures for handling chemicals should be followed.
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing.
Wash hands before breaks and at the end of work.
Do not inhale gases / fumes / aerosols.

· Engineering controls: Provide adequate ventilation.

· Breathing equipment:

Wear appropriate NIOSH respirator when ventilation is inadequate and occupational exposure limits are exceeded.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Gloves should provide protection from freezing temperatures.

· Eye protection:



Safety glasses

Follow relevant national guidelines concerning the use of protective eyewear.

· Body protection: Protective work clothing

· Limitation and supervision of exposure into the environment

No relevant information available.

· Risk management measures No relevant information available.

(Cont'd. on page 8)

Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: January 02, 2020

Trade name: CCASA-WFTC
CARB COMPLIANT ADHESIVE WEB FAST TACK

(Cont'd. of page 7)

9 Physical and chemical properties

· Information on basic physical and chemical properties	
· Appearance:	
Form:	Aerosol
Color:	According to product specification
· Odor:	Characteristic
· Odor threshold:	Not determined.
· pH-value:	Not determined.
· Melting point/Melting range:	Not applicable, as aerosol.
· Boiling point/Boiling range:	Not applicable, as aerosol.
· Flash point:	Extremely flammable aerosol.
· Flammability (solid, gaseous):	Not applicable.
· Auto-ignition temperature:	Not determined.
· Decomposition temperature:	Not determined.
· Danger of explosion:	Not determined.
· Explosion limits	
Lower:	Not determined.
Upper:	Not determined.
· Oxidizing properties:	Not determined.
· Vapor pressure at 20 °C (68 °F):	3102-4482 hPa (2326.7-3361.8 mm Hg)
· Density:	
Relative density:	Not determined.
Vapor density:	Not determined.
Evaporation rate:	Not applicable.
· Solubility in / Miscibility with	
Water:	Not determined.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity	
Dynamic:	Not determined.
Kinematic:	10-600 mm ² /s
· Other information	No relevant information available.

10 Stability and reactivity

- **Reactivity:** No relevant information available.
- **Chemical stability:** Stable under normal temperatures and pressures.
- **Thermal decomposition / conditions to be avoided:**
 Danger of receptacles bursting because of high vapor pressure if heated.
- **Possibility of hazardous reactions**
 Develops readily flammable gases / fumes.

(Cont'd. on page 9)



Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: January 02, 2020

Trade name: CCASA-WFTC
CARB COMPLIANT ADHESIVE WEB FAST TACK

(Cont'd. of page 8)

Can form explosive mixtures in air if heated above flash point and/or when sprayed or atomized.

Extremely flammable aerosol.

Reacts violently with oxidizing agents.

Reacts with strong acids and alkali.

Toxic fumes may be released if heated above the decomposition point.

· **Conditions to avoid** Excessive heat.

· **Incompatible materials** Oxidizers

· **Hazardous decomposition products**

Under fire conditions only:

Carbon monoxide and carbon dioxide

Danger of toxic fluorine based pyrolysis products.

11 Toxicological information

· **Information on toxicological effects**

· **Acute toxicity:** Based on available data, the classification criteria are not met.

· **LD/LC50 values that are relevant for classification:** None.

· **Primary irritant effect:**

· **On the skin:** Based on available data, the classification criteria are not met.

· **On the eye:** Irritating effect.

· **Sensitization:** Sensitization possible through skin contact.

· **IARC (International Agency for Research on Cancer):**

Present in trace quantities.

71-43-2	Benzene	1
91-20-3	Naphthalene	2B
98-82-8	Cumene	2B
100-41-4	Ethylbenzene	2B

· **NTP (National Toxicology Program):**

Present in trace quantities.

71-43-2	Benzene
91-20-3	Naphthalene
98-82-8	Cumene

· **OSHA-Ca (Occupational Safety & Health Administration):**

Present in trace quantities.

71-43-2	Benzene
---------	---------

· **Probable route(s) of exposure:**

Inhalation.

Eye contact.

Skin contact.

· **Germ cell mutagenicity:** Based on available data, the classification criteria are not met.

· **Carcinogenicity:** Based on available data, the classification criteria are not met.

· **Reproductive toxicity:** Based on available data, the classification criteria are not met.

· **STOT-single exposure:** May cause drowsiness or dizziness.

· **STOT-repeated exposure:** Based on available data, the classification criteria are not met.

· **Aspiration hazard:** May be fatal if swallowed and enters airways.

(Cont'd. on page 10)

Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: January 02, 2020

**Trade name: CCASA-WFTC
CARB COMPLIANT ADHESIVE WEB FAST TACK**

(Cont'd. of page 9)

12 Ecological information

- **Toxicity**
- **Aquatic toxicity**
Toxic to aquatic life with long lasting effects.

98-56-6 4-chloro- α,α,α -trifluorotoluene


EC50 (dynamic) 3 mg/kg (zebra fish)

- **Persistence and degradability** No relevant information available.
- **Bioaccumulative potential:** No relevant information available.
- **Mobility in soil:** No relevant information available.
- **Other adverse effects** No relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Contact waste processors for recycling information.
The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all relevant local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes.
- **Uncleaned packagings**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- **UN-Number**
- **DOT, ADR/RID/ADN, IMDG, IATA** UN1950
- **UN proper shipping name**
- **DOT** Aerosols
- **ADR/RID/ADN, IMDG** AEROSOLS
- **IATA** Aerosols, flammable
- **Transport hazard class(es)**
- **DOT**
- 
- **Class** 2.1
- **Label** 2.1

(Cont'd. on page 11)

Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: January 02, 2020

**Trade name: CCASA-WFTC
CARB COMPLIANT ADHESIVE WEB FAST TACK**

(Cont'd. of page 10)

· **ADR/RID/ADN**



· **Class** 2 5F
· **Label** 2.1

· **IMDG, IATA**



· **Class** 2.1
· **Label** 2.1

· **Packing group** Aerosols are not assigned a packing group.

· **Environmental hazards** Product contains environmentally hazardous substances: Heptane, 4-chloro- α,α,α -trifluorotoluene

· **Marine pollutant:**



Yes

· **Special precautions for user** Warning: Gases
· **Hazard identification number (Kemler code):** -
· **EMS Number:** F-D,S-U
· **Segregation groups** Liquid halogenated hydrocarbons

· **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code** Not applicable.

· **Transport/Additional information:**

· **DOT**



Limited Quantity for packages less than 30 kg gross and inner packagings less than 1 L.

· **ADR/RID/ADN**



Limited Quantity for packages less than 30 kg gross and inner packagings less than 1 L.

· **IMDG**

(Cont'd. on page 12)

Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: January 02, 2020

**Trade name: CCASA-WFTC
CARB COMPLIANT ADHESIVE WEB FAST TACK**

(Cont'd. of page 11)



Limited Quantity for packages less than 30 kg gross and inner packagings less than 1 L.

· IATA



Limited Quantity for packages less than 30 kg gross and inner packagings less than 1 L.

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- United States (USA)
- SARA

· **Section 302 (extremely hazardous substances):**

None of the ingredients are listed.

· **Section 355 (extremely hazardous substances):**

None of the ingredients are listed.

· **Section 313 (Specific toxic chemical listings):**

None of the ingredients are listed.

· **TSCA (Toxic Substances Control Act)**

All ingredients are listed or exempt.

· **Proposition 65 (California)**

· **Chemicals known to cause cancer:**

Present in trace quantities.

98-56-6	4-chloro- α,α,α -trifluorotoluene
---------	--

71-43-2	Benzene
---------	---------

91-20-3	Naphthalene
---------	-------------

98-82-8	Cumene
---------	--------

100-41-4	Ethylbenzene
----------	--------------

· **Chemicals known to cause developmental toxicity for females:**

None of the ingredients are listed.

· **Chemicals known to cause developmental toxicity for males:**

Present in trace quantities.

71-43-2	Benzene
---------	---------

110-54-3	n-Hexane
----------	----------

· **Chemicals known to cause developmental toxicity:**

Present in trace quantities.

67-56-1	methanol
---------	----------

(Cont'd. on page 13)

Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: January 02, 2020

**Trade name: CCASA-WFTC
CARB COMPLIANT ADHESIVE WEB FAST TACK**

(Cont'd. of page 12)

71-43-2	Benzene	
108-88-3	Toluene	

· **EPA (Environmental Protection Agency):**

67-64-1	Acetone	I
142-82-5	Heptane	D

· **IARC (International Agency for Research on Cancer):**

Present in trace quantities.

71-43-2	Benzene	1
91-20-3	Naphthalene	2B
98-82-8	Cumene	2B
100-41-4	Ethylbenzene	2B

· **Canadian Domestic Substances List (DSL):**

All ingredients are listed or exempt.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Abbreviations and acronyms:**

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road
 IMDG: International Maritime Code for Dangerous Goods
 DOT: US Department of Transportation
 IATA: International Air Transport Association
 CAS: Chemical Abstracts Service (division of the American Chemical Society)
 LC50: Lethal concentration, 50 percent
 LD50: Lethal dose, 50 percent
 OSHA: Occupational Safety & Health Administration
 Flam. Gas 1: Flammable gases – Category 1
 Flam. Aerosol 1: Aerosols – Category 1
 Press. Gas: Gases under pressure – Compressed gas
 Flam. Liq. 2: Flammable liquids – Category 2
 Flam. Liq. 3: Flammable liquids – Category 3
 Skin Irrit. 2: Skin corrosion/irritation – Category 2
 Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A
 Eye Irrit. 2B: Serious eye damage/eye irritation – Category 2B
 Skin Sens. 1: Skin sensitisation – Category 1
 Skin Sens. 1B: Skin sensitisation – Category 1B
 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
 Asp. Tox. 1: Aspiration hazard – Category 1

· **Sources**

Website, European Chemicals Agency (echa.europa.eu)
 Website, US EPA Substance Registry Services (ofmpub.epa.gov/sorinternet/registry/substreg/home/overview/home.do)
 Website, Chemical Abstracts Registry, American Chemical Society (www.cas.org)
 Patty's Industrial Hygiene, 6th ed., Rose, Vernon, ed. ISBN: 978-0-470-07488-6
 Casarett and Doull's Toxicology: The Basic Science of Poisons, 8th Ed., Klaassen, Curtis D., ed., ISBN: 978-0-07-176923-5.
 Safety Data Sheets, Individual Manufacturers

SDS Prepared by:

(Cont'd. on page 14)



Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: January 02, 2020

**Trade name: CCASA-WFTC
CARB COMPLIANT ADHESIVE WEB FAST TACK**

(Cont'd. of page 13)

ChemTel Inc.
1305 North Florida Avenue
Tampa, Florida USA 33602-2902
Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573
Website: www.chemtelinc.com